

# SolarEdge Home Load Controller

Model: DCS



SMART ENERGY

## Optimize energy consumption by controlling appliance usage

- / Controls permanently connected appliances
- / Includes two simultaneously controlled dry contact switches
- / Switches larger single and three phase loads via an external contactor
- / Wireless connection to the inverter via SolarEdge Home Network
- / Increases savings by maximizing self-consumption through improved utilization of excess PV
- / Optimizes backup operation by switching off non-essential loads
- / Designed to control heat pumps using a single stage SG-ready interface to enable excess PV activation and control operation during backup\*
- / Seamlessly integrates into the SolarEdge Home ecosystem
- / Offers a single source for warranty, support, and training, to streamline logistics and operations

\* Support for excess PV activation and backup control requires adding two Load Controllers.

# / SolarEdge Home Load Controller

Model: DCS

	SEM-DCS-R08-00	UNITS
<b>POWER</b>		
AC Input Voltage	90 – 250	Vac
AC Frequency	50 / 60	Hz
Normally Open (NO) Contact Specifications	250 Vac up to 8 Aac / 30 Vdc up to 8 Adc	
Normally Closed (NC) Contact Specifications	250 Vac up to 4 Aac / 30 Vdc up to 4 Adc	
Relay Switching Cycles	> 20,000	
Operating Hours	50,000	hr
Installation Altitude	2000	m
Power Consumption	< 1.5	W
<b>ENVIRONMENTAL</b>		
Operating Temperature	-10 to +50	°C
Storage Temperature	-20 to +60	°C
Relative Humidity (non-condensing)	0 – 95	%
Ingress Protection	IP30	
<b>INSTALLATION SPECIFICATIONS</b>		
Compatible SolarEdge Inverters	Residential inverters with SetApp configuration, including: SolarEdge Home Genesis Inverters (Australia only), SolarEdge Home Hub Inverters, SolarEdge Home Wave Inverters, SolarEdge Short String Inverters, SolarEdge Three Phase Inverters (SE16K and SE17K)	
Dimensions L x W x H	100 x 50 x 35 Excluding din-rail adapter	mm
<b>COMMUNICATION</b>		
Supported Communication Protocol	SolarEdge Home Network	
Device Configuration	Monitoring platform/app or SetApp; Ethernet connection is required	
Operating Frequency Range	863 – 870 (EU) 916 – 924 (AUS)	MHz
Modulation	O-QPSK (Quadrature phase shift keying)	
EIRP with Antenna	14 (EU) 20 (AUS)	dBm
<b>TEMPERATURE SENSOR</b>		
Ambient Temperature Sensing Accuracy	±0.5	°C
<b>ACCESSORIES</b>		
Included Mounting Materials	Wood screws, Double-sided tape Rail Mounting: Din-Rail adapter according to IEC/EN 60715	
<b>STANDARD COMPLIANCE</b>		
Applicable Safety Standards	IEC 60730-1:2013+AMD1:2015+AMD2:2020 CSV; UL 916:2021 Ed.5; UL 60730-1:2016 Ed.5; CSA E60730-1:2015 Ed.5	
EMC Standards	IEC/UL/EN 60730-1; EN 301 489-1; EN 301 489-3; EN 61000-3-2; EN 61000-3-3; FCC Part 15, Class B	
Radio Standards	EN 300 220; FCC 15.247C	
Regulation Mark	CE; ETL	

## CONNECTION DIAGRAM



Contacts switch simultaneously