

For sealed heating installations (acc. to EN12828) and chilled water (cooling) installations.

Expansion vessels keep the pressure of the installation stable by temporarily absorbing the extra water volume that is generated by heating or cooling installations.




Advantages


- Sustainable expansion vessels thanks to innovative technology.
- The Flexcon Premium expansion vessels have a plastic membrane (12 - 35 litres) made of thermoplastic polyolefin (TPO). The new membrane has a high flexibility and low permeability. The environmental performance of the new membrane is much better and TPO can be burned cleaner or recycled into products more effectively.
- The plastic membrane is much lighter because it requires up to 50% less material. This saves raw materials, energy (production) and fuel (transport) and results in a large reduction of CO2 emissions.
- The box is made from FSC certified cardboard and the version with the lowest available CO2 footprint has been selected.
- A long service life is guaranteed with a 15-year warranty and therefore also saves on maintenance.
- Extremely low permeability of the diaphragm ensures that pre-charge pressure is maintained for longer.
- The flexible diaphragms, with rolling action, are preformed and, in contrast to a bag type bladder, prevent stretching so that their properties are preserved over the long term.
- The two halves of the vessel are coated prior to assembly, not afterwards. Therefore there is no risk of corrosion on the clamp ring and the diaphragm does not have a service life-reducing thermal shock during production.
- The unique zinc plated steel clench ring construction clamps the diaphragm between the two deep drawn steel vessel halves. This not only ensures a perfect seal but also prevents mechanical damage of the diaphragm during use (load distribution over the entire clamping area and not at 1 central suspension point).
- The gas side is filled with nitrogen, and not with air, so that corrosion is prevented and the pressure loss is even more limited.
- The nitrogen air valve is countersunk on the vessel to protect it from damage, it is in turn further protected by a cover plate from recycled plastic.
- The ribbed profile on the diaphragm prevents it from sticking to the inside wall of the vessel and ensures inflow of expansion water at the slightest increase in pressure.
- The uncoated taper water connection thread ensures easy and water tight installation.
- Finished with a gleaming epoxy-powder coating.
- Each vessel is functionally tested before it leaves the factory.

Technical Specifications

- Maximum working pressure: 3.0.
- Vessels in accordance with EN13831.
- Suitable for systems with a maximum system temperature of 110 °C.
- Min./ max. temperature diaphragm: -10 / 70 °C.
- Suitable for addition of glycol-based anti-freeze up to 50%.
- In accordance with Pressure Equipment Directive 2014/68/EU.
- Red (RAL 3002) epoxy powder coating (18 and 25 litres also available in white).

- Flexcon Premium 35: With feet and including mounting kit.



Type	Capacity [l]	Pre-charge [bar]	Dimensions				Diaphragm	Syst. conn. (E)	Weight [kg]		Order Code
			A [mm]	B [mm]	Ø C [mm]	D [mm]					
Flexcon Premium 8/0.5 [3bar]	8	0.5	245	277	-	-	Butyl	R $\frac{3}{4}$ "	2.2	77	16913
Flexcon Premium 12/0.5 [3bar]	12	0.5	286	309	-	-	TPO	R $\frac{3}{4}$ "	2.7	60	16914
Flexcon Premium 12/1.0 [3bar]	12	1.0	286	309	-	-	TPO	R $\frac{3}{4}$ "	2.7	60	16915
Flexcon Premium 18/0.5 [3bar]	18	0.5	286	381	-	-	TPO	R $\frac{3}{4}$ "	3.4	48	16916
Flexcon Premium 18/1.0 [3bar]	18	1.0	286	381	-	-	TPO	R $\frac{3}{4}$ "	3.4	48	16917
Flexcon Premium 18/1.5 [3bar]	18	1.5	286	381	-	-	TPO	R $\frac{3}{4}$ "	3.4	48	16918
Flexcon Premium 18/0.5 [3bar] white	18	0.5	286	381	-	-	TPO	R $\frac{3}{4}$ "	3.4	48	16919
Flexcon Premium 18/1.0 [3bar] white	18	1.0	286	381	-	-	TPO	R $\frac{3}{4}$ "	3.4	48	16920
Flexcon Premium 25/0.5 [3bar]	25	0.5	328	402	-	-	TPO	R $\frac{3}{4}$ "	4.3	25	16922
Flexcon Premium 25/1.0 [3bar]	25	1.0	328	402	-	-	TPO	R $\frac{3}{4}$ "	4.3	25	16923
Flexcon Premium 25/1.5 [3bar]	25	1.5	328	402	-	-	TPO	R $\frac{3}{4}$ "	4.3	25	16924
Flexcon Premium 25/1.0 [3bar] white	25	1.0	328	402	-	-	TPO	R $\frac{3}{4}$ "	4.3	25	16926
Flexcon Premium 35/0.5 [3bar]	35	0.5	396	435	263	118	TPO	R $\frac{3}{4}$ "	5.3	18	16928
Flexcon Premium 35/1.0 [3bar]	35	1.0	396	435	263	118	TPO	R $\frac{3}{4}$ "	5.3	18	16929
Flexcon Premium 35/1.5 [3bar]	35	1.5	396	435	263	118	TPO	R $\frac{3}{4}$ "	5.3	18	16930



**Find more information online:**

[Installation and operating instruction](#)

[Declaration of conformity PED 2014/68/EU](#)

[CE Declaration of Conformity Module A](#)

[CE Declaration of Conformity Module B](#)

[UKCA Declaration of conformity](#)

[UKCA Declaration of Conformity Module A](#)

[UKCA Declaration of Conformity Module B](#)

[Flexcon Premium 12L EPD](#)

[Flexcon Premium 18L EPD](#)

[Flexcon Premium 25L EPD](#)

[Flexcon Premium 35L EPD](#)

[Flexcon Premium 8 - 35 DWG](#)

[Flexcon Premium 8 - 35 STEP](#)

[Flexcon Premium 8 - 35 RFA](#)

[Leaflet](#)

[Brochure Life cycle assessment Flexcon Premium](#)

[White paper - A half is more than one](#)

[Packaging data](#)

[Install video Flexcon Premium](#)

Fort Blauwkapel 1
1358 DB, Almere - nl

T +31 (0)36 52 62 300
E info@aalberts-hfc.com
I flamcogroup.com